

# EGL5055



## Features

- High Speed PCIe NVM Access
- GLI/BMM Compatible Security Boot

## Media Board

- Mini-ITX SBC
- NVIDIA 1050Ti Graphic Card
- 2.5" SSD Bay with Detection Log

## I/O System

- Intel® Atom™, Celeron®
- 1x DDR3L SO-DIMM, up to 8GB
- 2x SATA with Pin 7 VCC
- Up to 8 x USB + 6x Serial Port
- 3MB NVM up to 8MB
- 6x Door Intrusion Log
- 32x Isolation GPI + 32x High Current GPO
- 1x VGA
- Modular I/O Design
- Long Lifetime Support to 2029

## Headquarter

10F-3, No. 270, Sec. 4,  
Chung Hsiao E. Rd.,  
Taipei, 10694, Taiwan

T +886 2 2751-7192  
E-mail: [info@efco.com.tw](mailto:info@efco.com.tw)

## EMEA

T +49-991-2009298-0  
E-mail: [info@efcotec.com](mailto:info@efcotec.com)

## America

T +1-760-827-8600  
E-mail: [sales-us@efcotec.com](mailto:sales-us@efcotec.com)

**EFCO**  
EverFine Group

# EGL5055

---

| Model         | Description   |
|---------------|---|
| EGL5055-2     | <ul style="list-style-type: none"><li>• Intel® Atom® E3825 Dual Core, 1.3GHz, 1MB L2Cache)</li><li>• 1 x DDR3L-1067 SODIMM up to 8GB</li><li>• 2 x SATA with Pin 7 VCC</li></ul>    |
| EGL5055-N2930 | <ul style="list-style-type: none"><li>• Intel® Celeron® N2930 Quad Core, 2.16GHz, 2MB Cache</li><li>• 1 x DDR3L-1333 SODIMM up to 8GB</li><li>• 2 x SATA with Pin 7 VCC</li></ul>   |
| EGL5055-J1900 | <ul style="list-style-type: none"><li>• Intel® Celeron® J1900 Quad Core, 2.42GHz, 2MB L2Cache</li><li>• 1 x DDR3L-1333 SODIMM up to 8GB</li><li>• 2 x SATA with Pin 7 VCC</li></ul> |

## Headquarter

10F-3, No. 270, Sec. 4,  
Chung Hsiao E. Rd.,  
Taipei, 10694, Taiwan

T +886 2 2751-7192  
E-mail: [info@efco.com.tw](mailto:info@efco.com.tw)

## EMEA

T +49-991-2009298-0  
E-mail: [info@efcotec.com](mailto:info@efcotec.com)

## America

T +1-760-827-8600  
E-mail: [sales-us@efcotec.com](mailto:sales-us@efcotec.com)

