

# SmartSignage

The Fanless Digital Signage Player with Intel® Celeron® 4-core Processor J1900



## Features

- Fanless digital signage solution
- Low power consumption
- Supports Intel® Celeron® 4-core Processor J1900 (Bay Trail )
- Supports DDR3L SO-DIMM 1333 max. up to 8GB
- 1 x high definition video output & 1 x VGA or 2 x high definition video output
- 1 mSATA supported
- Supports VESA mount

| System                                   |   |
|--|---|
| CPU                                      | Intel® Celeron® 4-core Processor J1900 (Bay Trail)  |
| Storage                                  | 1 x mSATA supported   |
| Chipset                                  | SoC integrated  |
| System Memory                            | 1 x DDR3L 1333 max up to 8GB  |
| Watchdog                                 | 255 levels, 1-255 sec.  |
| I/O                                      |   |
| Audio                                    | MP3, WebM .ogg vorbis   |
| WiFi                                     | Optional for 802.11 b/g/n   |
| Video                                    | MPEG-4, MPEG-2, MPEG-1, H.264, WMV/VC1 (MPEG-2 ex/ps/ts.mp4, mov), WebM VP8/VP9 (8-12Mbit/s) 1080i/p @18-30 Mbit/s, 25 fps<br>EBC-3311: 1 x High definition video output 1 x VGA<br>EBC-3311B: 2 x High definition video output |
| Image Format                             | Jpeg, tiff, png, (anim) gif, bmp  |
| Expansion                                |   |
| PCIe                                     | 1 x full-size Mini card (for mSATA)<br>1 x half-size PCI Express Mini card for optional WiFi module   |
| Environment & Mechanical                 |   |
| Power Supply                             | 12V DC-in   |
| Weight (net/gross)                       | 0.7kg(1.5lb)/1.2kg(2.61b)   |
| Dimension(W x D x H)                     | 170 x 120 x 40 mm (6.69 x 4.72 x 1.57")   |
| Packing Dimension(W x D x H)             | 320 x 205 x 65 mm (12.59 x 8.07 x 2.55")  |
| Operating Temperature                    | 0°C – +40°C,(32°F – 104°F)  |
| Operating Humidity                       | 10% – 90% (non-condensing)  |
| Certification & Optional OS Installation |   |
| OS                                       | Windows® 7 Professional 64bit with SP1<br>Windows® Embedded Standard 7 64bit with SP1<br>Linux Ubuntu 14.04.3 LTS 64bit   |
| Certification                            | CE / FCC class A  |

## Headquarter

10F-3, No.270, Sec.4,  
Chung Hsiao E. Rd.,  
Taipei, 10694, Taiwan

T +886 2 2751-7192  
E-mail: info@efco.com.tw

## EMEA

T +49-991-2009298-0  
E-mail: info@efcotec.com

## America

T +1-760-827-8600  
E-mail: sales-us@efcotec.com

**EFCO**  
EverFine Group

Note : All product specifications are subject to change without notice

## Ordering Information

| Model    | Description  |
|----------|--|
| EBC-3311 | EBC-3311 Fanless Box PC/Intel® Celeron® J1900<br>Front Side <ul style="list-style-type: none"><li>◆ 1 x high definition video output</li><li>◆ 1 x USB 2.0</li><li>◆ 1 x USB 3.0</li><li>◆ 2 x 10/100/1000Mbps Ethernet</li><li>◆ 1 x power on/off button</li><li>◆ 1 x Audio (Line-Out)</li><li>• 12V Power input</li></ul> |

### Headquarter

10F-3, No. 270, Sec. 4,  
Chung Hsiao E. Rd.,  
Taipei, 10694, Taiwan

T +886 2 2751-7192  
E-mail: info@efco.com.tw

### EMEA

T +49-991-2009298-0  
E-mail: info@efcotec.com

### America

T +1-760-827-8600  
E-mail: sales-us@efcotec.com